

- 1 Unique identification code of the product-type: **Bituminous Corrugated Sheet**
- 2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): **Bituminous Corrugated Sheets of Category R „Guttanit“, „Gutta Do It“, „Guttapral“**
- 3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Bituminous Corrugated Sheets for roofing and wall cladding**
- 4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **Gutta Italia Srl.
Via L. Mascheroni, 4
I - 20123 Milano (MI)
www.gutta.com**
- 5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **not relevant**
- 6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
- 7 In case of the declaration of performance concerning a construction product covered by a harmonised standard: **Accredited Testing Authority for Materials, University Karlsruhe (KIT) performed the initial inspection and material testing under system 4 and issued certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation**
- 8 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **not relevant**

9 Declared performance:

Essential characteristics	Performance	Test standard	Harmonised technical specification
Bending under downward load	> 1400 N/m ²	EN 534 – Section 5.2.1	DIN EN 534:2010-07
Impact strength	400 mm	EN 534 – Section 5.2.2	
Tearing strength	> 200 N	EN 534 – Section 5.2.3	
Water impermeability	waterproof	EN 534 – Section 5.3.1	
Tearing strength after Freeze/thaw ageing	NPD	EN 534 – Section 5.4.1	
Water impermeability after Freeze/thaw ageing	waterproof	EN 534 – Section 5.4.2	
Thermal coefficient	$\alpha < 100 \times 10^{-6} \text{ 1/K}$	EN 534 – Section 5.4.3	EN 13501-1
Reaction to fire	E	EN 534 – Section 5.5.1	EN 13501-5
External fire performance	F	EN 534 – Section 5.5.2	
Dangerous substances	NPD		

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Nicola Bianchi – managing director

Filago, dated 24.06.13